

Lesen Sie die Gebrauchsanweisung vor der Verarbeitung aufmerksam durch.

Achtung:

Produkt nicht zulässig im Bereich der StVZO. Produkt ist daher nur für die Verwendung im Ausland bestimmt.

- 1 Schneiden Sie die HEADLIGHT-Folien mit 1 cm Übermaß entlang der Kontur des Scheinwerfers zu. Entfernen Sie die Schutzfolie der klebenden Seite und legen Sie die HEADLIGHT-Folie an einer Ecke des Scheinwerfers an. Erwärmen Sie die Folie und die zu beklebende Oberfläche vorsichtig mit einem Haartrockner. Achtung: eine zu starke Erwärmung kann die Folie beschädigen.
- 2 Ziehen Sie die erwärmte Folie vorsichtig über den Scheinwerfer und drücken Sie sie mit dem Daumen an. Schrittweise vorgehen und dabei einen Einschluss von Luftblasen vermeiden.
- 3 Drücken Sie die Kanten der Folie gut mit beiliegendem Rakel fest (nicht bei Version XENON) und schneiden Sie die überstehende Folie ab.

Please read the instruction manual carefully before usage.

Thoroughly clean the glass or plastic surface to be covered removing all dust, dirt or oil residue.

- 1 Cut the HEADLIGHT-Film following your headlights contours and allowing a 1 cm border. Remove the release liner and attach the film to an edge of the headlight. Warm the film and the surface to be covered lightly using the hair drier.

Caution: Warming the film too much will destroy it.

- 2 Apply the warmed film by stretching it and pressing it in place with your thumb. Working in steps apply the film evenly watching out for bubbles.
- 3 Finally, press the film into the corners and along edges using the squeegee included in the package (not with XENON film).

Special tips for applying XENON film:

A) For strongly bulging headlight glass cut and apply the film in two parts.

B+C) Use only the wet application process with XENON film. Remove the overhanging, excess film with the cutter knife.

D) Tip: The film can be applied in a pattern leaving uncovered spaces.

HEAD
LIGHT
FILM

FOLIATEC.com

MONAGEANLEITUNG • INSTALLATION INSTRUCTION

FOLIATEC BöhM GmbH & Co Vertriebs KG
Neumeyerstr. 70, 90411 Nürnberg, Germany
Tel.: +49(0)911/97544-0
Fax: +49(0)911/97544-333
techsupport@foliatec.de
www.foliatec.com